



Fanvil V50P Entry level Business IP phone

V50P is a stylish, high-performance entry-level IP phone with a 2.3-inch 132x64 pixel dot-matrix screen, support for 2 SIP lines and 6 way audio conference, support PoE power supply, and HD voice. It can meet the application scenarios of different enterprises, and provide users with excellent interaction and comfortable instant Internet communication experience.

Highlights

- ☒ 2.3-inch 132x64 pixel dot-matrix screen
- ☒ Support audio codec G.722 and Opus, HD audio on speakerphone and handset
- ☒ Support 6-way Audio Conference
- ☒ Available to link with security products, can be easily customized into various security solutions for reducing investment
- ☒ Fast Ethernet - 10/100Mbps Ethernet, integrated PoE
- ☒ HAC HD voice handset and full duplex hands-free speaker hardware configuration to provide users with an outstanding audio experience
- ☒ Two installation methods of desktop stand and wall mountable
- ☒ Compatible with EHS headset



Generic

- 132x64 pixel dot-matrix screen(No backlight)
- 2 SIP lines
- HD voice
- PoE enabled
- Handset / hands-free / headset mode
- Desktop Stand / Wall-mounted (optional)
- Optional external power supply
- Handset with Hall-effect Sensor Switch

- Action Plan
- Personalized ringtone settings
- Group listening

Call Features

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- BLF
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (With server)
- 6-way Audio Conference
- Hot Line
- IP direct dial
- Call back
- Hot Desking

Phone Features

- Local Phonebook (1000 entries)
- Remote Phonebook (XML/LDAP)
- Call logs (In/out/missed, 1000 entries)
- Blocked List/Allowed List
- Voice Message Waiting Indication (VMWI)
- Programmable Soft keys
- Network Time Synchronization
- Support Poly wireless headset (Through Poly APD-80 EHS Cable)
- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording(through server)
- Action URL / Active URI
- uaCSTA
- Dial Plan
- SIP Hotspot
- Multicast

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.726, G.729, G.729A, G.729B, G.729AB, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR) / Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)
- VQM voice quality monitoring

Network

- Physical: 10/100 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode:IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- CDP
- QoS
- Support SIP backup server
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Protocols

- SIP2.0 over UDP/TCP/TLS
- DNS A/SRV/NAPTR
- RTP/RTCP/SRTP
- STUN
- DHCP
- CDP
- LLDP
- PPPoE
- 802.1x
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069
- AES128 & AES256

Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

Physical Specifications

- LCD: 132x64 pixel dot-matrix screen
- Keypad: 24 keys, including
 - 3 Function keys (Mute, Headset, Redial)
 - 4 Soft-keys
 - 2 Navigation keys
 - 12 Standard Phone Digits keys
 - 2 Volume Control keys, Lower/Increase(Left/Right)
 - 1 Hands-free key
- HD Handset (RJ9) x1
- Handset with Hall Switch
- Standard RJ9 Handset Wire x1
- 1.5M CAT5.E Ethernet Cable x1
- Desk Stand x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- Security Slot x1
- Power: DC5V/1A or PoE
- Power Consumption(Adapter): 0.9~1.8W
- Power Consumption(PoE): 1.4~2.5W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation:
 - Desktop Stand
 - Wall-mounted (Optional)
- Color: Gunmetal
- Qty/CTN: 10pcs
- N.W/CTN: 8.25 kg
- G.W/CTN: 8.785kg
- Device Dimensions:
 - Desktop Stand (40°): 173.00x184.96x169.90 mm
 - Desktop Stand (45°): 173.00x173.93x177.96 mm
 - Wall mountable: 173.00x91.34x215.55 mm
- Gift Box Dimensions: 250x220x55 mm
- Outer CTN Dimensions: 460x300x270 mm (10 PCS)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products. For more information, please visit: www.fanvil.com

